

ASAP FASTENING SYSTEMS, INC.

SUPPLIES FOR INDUSTRY AND CONSTRUCTION

2013 SOUTH 37TH STREET • MILWAUKEE, WISCONSIN 53215

(414) 344-4500 • FAX (414) 344-4504

WWW.ASAPFASTENING.COM • EMAIL: SALES@ASAPFASTENING.COM

ATRAACE

WA-5000 Max. 2"



Advanced Technology Reducing Hole Drilling Cost



Features

- 2" x 3" hole drilling capacity
- Semi-automatic feed mechanism
- Powerful 1100 watt double insulated motor
- Overload stop detection system helps prevent motor and cutter damage
- Load detection system monitors and regulates motor speed and cutting feed
- Sealed arbor system with through spindle coolant
- Built-in motion detection sensor
- One-Touch arbor system "No tools required for cutter installation and removal"
- Accepts Jetbroach carbide tipped and Hibroach HSS annular cutters
- Precision machined die cast aluminum mainframe, motor slide and arbor support bracket
- One year limited warranty

Specifications

Model		WA-5000	
Power Source (Single Phase)	110 - 120 V AC 50 / 60 Hz	220 - 240 V AC 50 / 60 Hz	
Rated Power Consumption	1100		
	10.8		
	5.4		
Rated Current	300 / 600		
Max. Load Speed	rpm (Type)		
Rated Power Consumption	75		
Max. Drilling Capacity	Cutter	Hole Diameter	Plate Thickness
Overhead type JETBROACH HL	17.5 to 50 mm (1 1/8" to 2")	8 to 75 mm (3/8" to 3")	
Overhead type HIBROACH HL	14 to 50 mm (9/16" to 2")	8 to 30 mm (3/8" to 1")	
Rated Holding Force	kg (Lbs)	8,000 (1,000) (3,000)	
Rated Dimensions	mm (Inches)	101 x 304 (4" x 8")	
Max. Weight	kg (Lbs)	20 (50)	

Semi-Automatic Feed

Activates simply by positioning feed handles inward toward machine frame



Standard Accessories

- 2" pilot pin #UEA0550-0
- Safety chain
- Motor-side handle
- 3 mm allen wrench
- 8 x 10 mm combination wrench
- Sample cutting fluid
- Molded plastic carrying case