

ASAP FASTENING SYSTEMS, INC.

SUPPLIES FOR INDUSTRY AND CONSTRUCTION

2013 SOUTH 37TH STREET • MILWAUKEE, WISCONSIN 53215

(414) 344-4500 • FAX (414) 344-4504

WWW.ASAPFASTENING.COM • EMAIL: SALES@ASAPFASTENING.COM

UA-100

STUD WELDING CONTROL/TIMER UNIT*

Specifications

Height 11-3/4"
Width 11-1/2"
Depth 10"
Weight 25 lbs.

Stud Welding Range

12 ga. (2.6 mm) through 5/8" (16 mm)

Calibrated Time Control

Continuously adjustable from
.05 to 1.2 seconds

Features

Lightweight and rugged steel enclosure.
Plug in circuitry making all components
field serviceable.
Solid state timer allows for repeatability
and dependability.
Power on safety switch and accessible
front panel fuse.



UA 100 system comes complete with control unit,
stud welding gun with legs and foot piece.
50 ft. of 1/0 combination cable,
25 ft. of 1/0 generator cable, and
25 ft. of 1/0 ground cable with "C" clamp.

NOTE: CONTROL/TIMER UNIT REQUIRES EXTERNAL DC AND OPEN CIRCUIT VOLTAGE POWER INPUT
SUFFICIENT FOR DIAMETER OF STUD TO BE WELDED