

ASAP FASTENING SYSTEMS, INC.

SUPPLIES FOR INDUSTRY AND CONSTRUCTION


2013 SOUTH 37TH STREET • MILWAUKEE, WISCONSIN 53215

(414) 344-4500 • FAX (414) 344-4504

WWW.ASAPFASTENING.COM • EMAIL: SALES@ASAPFASTENING.COM

Dimensional Data

HEAVY HEX BOLTS



| Nominal Diameter | | D | WF | | | WC | | H | | | R | |
|------------------|---------|----------|--------------------|-------|-------|----------------------|-------|-------------|-------|-------|------------------|------|
| | | Body Dia | Width Across Flats | | | Width Across Corners | | Head Height | | | Radius of Fillet | |
| Fractional | Decimal | Max | Basic | Max | Min | Max | Min | Basic | Max | Min | Max | Min |
| 1/2 | 0.5000 | 0.515 | 7/8 | 0.875 | 0.850 | 1.010 | 0.969 | 11/32 | 0.364 | 0.302 | 0.03 | 0.01 |
| 5/8 | 0.6250 | 0.642 | 1- 1/16 | 1.062 | 1.031 | 1.227 | 1.175 | 27/64 | 0.444 | 0.378 | 0.06 | 0.02 |
| 3/4 | 0.7500 | 0.768 | 1- 1/4 | 1.250 | 1.212 | 1.443 | 1.383 | 1/2 | 0.524 | 0.455 | 0.06 | 0.02 |
| 7/8 | 0.8750 | 0.895 | 1 -7/16 | 1.438 | 1.394 | 1.660 | 1.589 | 37/64 | 0.604 | 0.531 | 0.06 | 0.02 |
| 1 | 1.0000 | 1.022 | 1 -5/8 | 1.625 | 1.575 | 1.876 | 1.796 | 43/64 | 0.700 | 0.591 | 0.09 | 0.03 |
| 1-1/8 | 1.1250 | 1.149 | 1-13/16 | 1.812 | 1.756 | 2.093 | 2.002 | 3/4 | 0.780 | 0.658 | 0.09 | 0.03 |
| 1-1/4 | 1.2500 | 1.277 | 2 | 2.000 | 1.938 | 2.309 | 2.209 | 27/32 | 0.876 | 0.749 | 0.09 | 0.03 |
| 1-3/8 | 1.3750 | 1.404 | 2- 3/16 | 2.188 | 2.119 | 2.526 | 2.416 | 29/32 | 0.940 | 0.810 | 0.09 | 0.03 |
| 1-1/2 | 1.5000 | 1.531 | 2- 3/8 | 2.375 | 2.300 | 2.742 | 2.622 | 1 | 1.036 | 0.902 | 0.09 | 0.03 |
| 1-3/4 | 1.7500 | 1.785 | 2- 3/4 | 2.750 | 2.662 | 3.175 | 3.035 | 1- 5/32 | 1.196 | 1.054 | 0.12 | 0.04 |
| 2 | 2.0000 | 2.039 | 3- 1/8 | 3.125 | 3.025 | 3.608 | 3.449 | 1-11/32 | 1.388 | 1.175 | 0.12 | 0.04 |
| 2-1/4 | 2.2500 | 2.305 | 3- 1/2 | 3.500 | 3.388 | 4.041 | 3.862 | 1- 1/2 | 1.548 | 1.327 | 0.19 | 0.06 |
| 2-1/2 | 2.5000 | 2.559 | 3- 7/8 | 3.875 | 3.750 | 4.474 | 4.275 | 1-21/32 | 1.708 | 1.479 | 0.19 | 0.06 |
| 2-3/4 | 2.7500 | 2.827 | 4- 1/4 | 4.250 | 4.112 | 4.907 | 4.688 | 1-13/16 | 1.869 | 1.632 | 0.19 | 0.06 |
| 3 | 3.0000 | 3.081 | 4- 5/8 | 4.625 | 4.475 | 5.340 | 5.102 | 2 | 2.060 | 1.815 | 0.19 | 0.06 |

Note: L = Length of Bolt