

ASAP FASTENING SYSTEMS, INC.

SUPPLIES FOR INDUSTRY AND CONSTRUCTION

2013 SOUTH 37TH STREET • MILWAUKEE, WISCONSIN 53215

(414) 344-4500 • FAX (414) 344-4504

WWW.ASAPFASTENING.COM • EMAIL: SALES@ASAPFASTENING.COM

ATRAACE UOJ-3500 Max. 1-3/8"

Designed to use **Jetbroach** Carbide Tipped Annular Cutters



Features

- 1-3/8" x 2" hole drilling capacity
- Designed to use **Jetbroach** carbide tipped annular cutters
- Lightweight 31 lb. design
- One (1) horsepower 700 rpm motor
- Reversible feed shaft assembly for left or right operation
- Sealed arbor with through spindle coolant
- Self contained in-frame coolant reservoir
- Built-in motion sensor detection sensor
- One-Touch arbor system "No tools required for cutter installation and removal"
- Precision machined die cast aluminum mainframe, motor, motor slide and arbor support bracket
- One year limited warranty



Uses **Jetbroach Carbide Tipped Annular Cutters**

Specifications

Model	UOJ-3500		
Power Source	110-120V		
Drill Motor	Power Consumption	W	680
	Rated Current	A	6
	No load Speed	rpm	700
Magnet Power Consumption	W	32	
Drilling capacity	Cutter	Diameter	Material Thickness
Hi-Broach High Speed Steel		1-3/8"	2" max
Twist Drill Capacity	inch	1/2"	
Magnet Holding Power	lbs.	2,023	
Magnet Dimensions	inch	3-5/32" x 6-3/8"	
Maximum Stroke	inch	3-3/4"	
Weight	lbs.	31	

Standard accessories

- Pilot pin #UEAD835-0
- Spanner
- 3 mm Allen wrench
- 5mm Allen wrench
- Safety chain
- Coolant sample
- Side handle
- 3 Feed handles
- Chip guard
- Molded plastic carrying case



Cutting in I-beams



Overlapped cutting



Edge hole cutting