


ASAP Fastening Systems Inc

Neoprene Inserts

Blind threaded fastener that has a brass threaded insert molded into a neoprene bushing. Made of synthetic rubber and resistant to most chemicals, oils, and weather conditions. You can install this insert into through holes or blind holes without tools of any kind. This fastener makes the joint waterproof, isolates vibration and is electrically insulated.



UNIFIED THREAD SIZES (inch)		Min-Max Grip	Hole Size (+.000 / -.006)	D. Nom (+.000 / -.006)	FD. Nom (+/- .006)	L. Nom (+/- .006)	FH. Nom (+/- .006)
Thread Size	Part Number						
6-32	FPCC632	0.375-0.607	.250	.240	.554	.981	.035
6-32	FPCE632	0.015-0.156	.312	.312	.452	.499	.062
8-32	FPCB832	0.015-0.156	.312	.312	.438	.499	.052
8-32	FPCC832	0.015-0.172	.312	.312	.750	.560	.060
8-32	FPC2D832	0.015-0.050	.312	.310	.500	.430	.050
10-24	FPCL1024	0.030-0.227	.375	.375	.562	.767	.187
10-32	FPC10S	0.015-0.192	.375	.375	.500	.554	.036
10-32	FPC10SL	0.312-0.643	.375	.375	.562	1.051	.051
10-32	FPC10XL	0.812-1.143	.375	.375	.562	1.551	.051
10-32	FPCG1032	0.030-0.227	.375	.375	.750	.807	.187
10-32	FPCH1032	0.312-0.450	.375	.375	.554	.847	.035
10-32	FPCJ1032	0.030-0.227	.375	.375	.750	.700	.080
10-32	FPCQ1032	0.035-0.232	.375	.375	.562	.665	.040
1/4-20	FPC1/4S	0.015-0.111	.500	.500	.630	.630	.051
1/4-20	FPCD1420	0.031-0.187	.500	.500	.750	.829	.187
1/4-20	FPCJ1420	0.250-0.457	.500	.500	.635	1.051	.051
5/16-18	FPCE51618	0.015-0.156	.625	.620	.875	.725	.125
5/16-18	FPCF51618	0.156-0.375	.625	.620	.875	1.100	.225
3/8-16	FPCA3816	0.015-0.437	.750	.750	1.250	1.062	.187

Phone 414-344-4500 Fax 414-344-4504