

# ASAP FASTENING SYSTEMS, INC.

SUPPLIES FOR INDUSTRY AND CONSTRUCTION

2013 SOUTH 37TH STREET • MILWAUKEE, WISCONSIN 53215


(414) 344-4500 • FAX (414) 344-4504

WWW.ASAPFASTENING.COM • EMAIL: SALES@ASAPFASTENING.COM

## Self-Clinch Standoffs

## Blind Threaded Style

303  
Stainless



SELF-CLINCHING STANDOFFS -- 303 STAINLESS STEEL													
Body Code & Thread Size	S		H		Hole Size in Sheet		Distance from center line of hole to edge of sheet	Min. Sheet Thickness	Performance in .060 in. thick 5052 Aluminum				
	Shank Outside Diameter		Hex Head Dimension						Installation Force	Pushout	Torque Out	Axial Pull Through	Recommended Tightening Torque for Waring Screw (In. Lbs.)
	Max	Min	Max	Min	Max	Min	Min	Inches	Lbs.	Lbs.	In. Lbs.	Lbs.	Max
4-40	.165	.160	.192	.182	.169	.166	.234	.040	1075	155	10	220	3.8
6-40	.212	.207	.192	.182	.216	.213	.266	.040	1680	290	24	235	3.8
6-32	.212	.207	.255	.245	.216	.213	.266	.040	1680	290	24	235	7
8-32	.280	.275	.317	.307	.284	.281	.312	.050	2350	400	25	248	7
8-32	.280	.275	.317	.307	.284	.281	.312	.050	2400	400	45	464	14
10-32	.280	.275	.317	.307	.284	.281	.312	.050	2400	400	45	464	25
Tolerance on Length							+ .002, - .005						

<b>Description</b>	A cylindrical fastener with a low-profile, hexagon-shaped head. The end opposite the head is internally threaded. It is considered a "blind" fastener because the threaded section does not extend through the entire length of the standoff. Immediately below the head is a slight indentation that extends completely around the item's circumference. This indentation, or groove, provides the clinching action when the part is pressed thru a properly sized hole in sheet metal.
<b>Applications / Advantages</b>	The standoff becomes permanently set when squeezed into place into a proper size drilled or punched hole. After it is pressed into place, the standoff forms a flush surface with the sheet metal.
<b>Material</b>	303 Stainless Steel, passivated to ASTM A 380 specifications
<b>For use in...</b>	...materials with a hardness of Rockwell B70 or less.
<b>Finish</b>	Stainless self-clinching standoffs usually do not have any additional finish.

# ASAP FASTENING SYSTEMS, INC.

SUPPLIES FOR INDUSTRY AND CONSTRUCTION

2013 SOUTH 37TH STREET • MILWAUKEE, WISCONSIN 53215


(414) 344-4500 • FAX (414) 344-4504

WWW.ASAPFASTENING.COM • EMAIL: SALES@ASAPFASTENING.COM

**303  
Stainless**

**Thread Length**

**Self-Clinch Standoffs**



**LENGTH OF THREAD FOR SELF-CLINCHING STANDOFFS**

Part #	Body Code (if app.) x Thread x Length	T	Part #	Body Code (if app.) x Thread x Length	T	Part #	Body Code (if app.) x Thread x Length	T
		Thread Length			Thread Length			Thread Length
040506SCBSOS	6-4-40 x 5/16	.156	060506SCBSOS	8-6-32 x 5/16	.156	0805SCBSOS	8-32 x 5/16	.156
0405SCBSOS	4-40 x 5/16	.156	0605SCBSOS	6-32 x 5/16	.156	0806SCBSOS	8-32 x 3/8	.156
040606SCBSOS	6-4-40 x 3/8	.156	060606SCBSOS	8-6-32 x 3/8	.156	0807SCBSOS	8-32 x 7/16	.187
0406SCBSOS	4-40 x 3/8	.156	0606SCBSOS	6-32 x 3/8	.156	0808SCBSOS	8-32 x 1/2	.250
040706SCBSOS	6-4-40 x 7/16	.187	060706SCBSOS	8-6-32 x 7/16	.187	0809SCBSOS	8-32 x 9/16	.250
0407SCBSOS	4-40 x 7/16	.187	0607SCBSOS	6-32 x 7/16	.187	0810SCBSOS	8-32 x 5/8	.250
040806SCBSOS	6-4-40 x 1/2	.250	060806SCBSOS	8-6-32 x 1/2	.250	1105SCBSOS	10-32 x 5/16	.156
0408SCBSOS	4-40 x 1/2	.250	0608SCBSOS	6-32 x 1/2	.250	1106SCBSOS	10-32 x 3/8	.156
040906SCBSOS	6-4-40 x 9/16	.250	060906SCBSOS	8-6-32 x 9/16	.250	1107SCBSOS	10-32 x 7/16	.187
0409SCBSOS	4-40 x 9/16	.250	0609SCBSOS	6-32 x 9/16	.250	1108SCBSOS	10-32 x 1/2	.250
041006SCBSOS	6-4-40 x 5/8	.250	061006SCBSOS	8-6-32 x 5/8	.250	1109SCBSOS	10-32 x 9/16	.250
0410SCBSOS	4-40 x 5/8	.250	0610SCBSOS	6-32 x 5/8	.250	1110SCBSOS	10-32 x 5/8	.250